



product details

EKINOS F OSTAR

Product description: EKINOS F OSTAR
 Product code: 4008321273758
 Quantity: Shipping carton box (VS) contains
 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321273758

Applications				
Type of connection	FIXED CONNECTION (TERMINAL)			
Categorizations				
SEG number	7459570			
Certificates & Standards				
Type of protection	IP20			
Protection class	I			
General Description				
Recycling	Yes			
Reflector type	LENS			
Equipment	LED COINLIGHT OSTAR			
Number of lighting outlets	1			
Cover material	PC (POLYCARBONATE)			
Type of cover	SECONDARY LENS			
Body material	ALUMINIUM			
Technical - Colors				
Product color	SILVER			
Technical - Electrical Data				
Operating mode	ELECTRONIC CONTROL GEAR (ECG)			
Nominal current	0.07 A			
Mains frequency	50...60 Hz			
Nominal voltage	230 V			
Nominal wattage	15 W			
Technical - Geometries				
Height	170.00 mm			
Width	120.00 mm			
Length	120.00 mm			
Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4008321273758	Shipping carton box contains 1 Piece	180,000 mm x 170,000 mm x 390,000 mm	1.330,000 g (0,000 g)	11,934 Cubic dec.



product details

EKINOS F OSTAR

EKINOS OSTAR

With its attractive design, EKINOS OSTAR is the perfect decorative indoor spot. There's no heat emission on the lighted object, and it has a very long lifetime (about 30,000 hours).

EKINOS OSTAR is perfect for highlighting output. Accent lighting in hotels, restaurants, shops, lighting shows, galleries, museums, or simply for decorative domestic lighting.

- An aluminum body, painted gray
- Equipped with COINlight-OSTAR 12 W inside
- EKINOS E OSTAR (recessed version) delivered without power supply, but with a male connector and EKINOS F OSTAR (visible version) with power supply OT 20/120-240/24 S
- For recessed and visible mounting
- Power supply kit for 1 or 6 spots (necessary for EKINOS E OSTAR)
- CE-sign Beam angle 38°, not dimmable, IK05, IP20