



product details

80222-21 DRAGONSPOT SHORT 854



Product description: 80222-21 DRAGONSPOT SHORT 854
 Product code: 4008321326232
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321326232

Applications	
Accessories	DRAGONSPOT CONNECTION KIT 9 W (4008321326201)
Adjustable	Yes
Type of connection	CABLE/CONNECTOR

Certificates & Standards	
Standards	CE
Protection against ignition and fire	F, MM
Type of protection	IP20
Glow Wire Test according to IEC 695-2-1	650 °C
Protection class	III

General Description	
Number of lighting outlets	1
Equipment	LED
Recycling	Yes
Equipped with lamp	Yes
Body material	ALUMINIUM

Technical - Colors	
Product color	BRUSHED

Technical - Electrical Data	
Nominal wattage	1.2 W
Nominal voltage	3.4 V
Mains frequency	50 Hz
Nominal current	350 mA
Operating mode	POWER LINE

Technical - Geometries	
Mounting diameter	11 mm
Diameter	27 mm
Mounting depth	35 mm
Length	165.50 mm
Width	38.00 mm
Height	32.00 mm

Technical - Light Technical Data	
Color rendering index Ra	80
Color temperature	3000 K
Beam angle	12 °

Technical - Temperatures	
Glow Wire Test according to IEC 695-2-1	650 °C





Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4008321326232	Folding carton box contains 1 Piece	70,000 mm x 57,000 mm x 173,000 mm	117,000 g (0,000 g)	0,690 Cubic dec.
4008321326249	Shipping carton box contains 4 Piece	153,000 mm x 131,000 mm x 186,000 mm	587,333 g (0,000 g)	3,728 Cubic dec.

DRAGONSPOT

DRAGONSPOT is a miniaturized luminaire with an adjustable head. It is especially suitable as a bedtime reading light, for attaching to wardrobes to dress by, or for spotlighting pictures. Equipped with a powerful and efficient Golden DRAGON LED.

- Aluminum casing, anodized and brushed
- Mounting diameter 10 mm, attached by means of a threaded connector at the back. The long version may be screwed instead.
- Two versions (long/short), 500 mm cable. Separate OT9/200-240V/350 DIM control gear including connecting terminal with up to 6 plug locations
- Equipped with 1 Golden DRAGON LED 1.2 W
- Average life 50,000 hours
- Color temperatures cold white (5400 K) and warm white (3000 K)
- CE Sign F Sign MM Sign Protection class III, IP20, Glow wire test at 650 °C, Ambient temperature from -10 °C to +40 °C, Mounting diameter 10 mm, 350 mA, Beam angle 12°, dimmable