



product details

DRAGONSPOT CONNECTION KIT 9W



Product description: DRAGONSPOT CONNECTION KIT 9W
 Product code: 4008321326201
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321326201

| Applications | |
|-------------------|----------|
| Dimming interface | 1...10 V |
| Dimmable | Yes |

| Categorizations | |
|-----------------|---------|
| SEG number | 7459587 |

| Certificates & Standards | |
|--------------------------|----|
| EEL - Energy Label | A1 |
| Standards | CE |

| General Description | |
|---------------------|-----|
| Recycling | Yes |

| Packaging units | | | | |
|-----------------|--------------------------------------|--------------------------------------|-----------------------|------------------|
| Product code | Packaging type and content | Dimensions in h x w x l | Gross weight | Volume |
| 4008321326201 | Folding carton box contains 1 Piece | 78,000 mm x 61,000 mm x 230,000 mm | 214,000 g (0,000 g) | 1,094 Cubic dec. |
| 4008321326218 | Shipping carton box contains 8 Piece | 152,000 mm x 128,000 mm x 472,000 mm | 1.927,000 g (0,000 g) | 9,183 Cubic dec. |

**Accessories for COLOR-e-MOTION Tube RGB**

The product is controlled via a Wallmount Unit (WMU), a complete easy-to-use system with an infrared remote control (the IR receiver is integrated in the WMU). Up to 3 groups of luminaires can be controlled individually via one WMU.

CE Sign

Accessories for COLOR-e-MOTION Tube EASY

DALI EASY remote control works according to the principle of mixing colors by adding colors, and is based on different channels: red, green, and blue.

CE Sign

Accessories for COLOR-e-MOTION Tube EASY

With the software EASY COLOR CONTROL, it is possible to set up 16 wallwashers in RGB or white. The temporization of every scene is independently adjustable: more quickly to awake and to stimulate or more slowly for more color and to dissimulate changes.

CE Sign

Accessories for COLOR-e-MOTION Panel RGB

The product is controlled via a Wallmount Unit (WMU), a complete easy-to-use system with an infrared remote control (the IR receiver is integrated in the WMU).

Mounting accessories for COLOR-e-MOTION Panel

Power is supplied via the OPTOTRONIC OT EASY 60/220-240/24 RGB electronic control gear. 16 ECGs can be combined, to each of which three COLOR-e-MOTION Panel units can be connected. This means that up to 48 luminaires can be synchronized. They are controlled via the IR remote control, IR switch, or software.

CE Sign

Power supply kit

- Power supply kit 60 W (can supply up to 3 COLOR-e-MOTION Panel)

Vertical mounting kit

- Vertical mounting kit (white or black) - it depends on the color of the panel
- The power supply is integrated in the hat peg

Horizontal mounting kit

- Horizontal mounting kit, with 4 cables for suspension and an electronic connection cable

Accessories for COLOR-e-MOTION Panel EASY

DALI EASY remote control works according to the principle of mixing colors by adding colors, and is based on different channels: red, green, and blue.

CE Sign

Accessories for COLOR-e-MOTION Panel EASY

With the software EASY COLOR CONTROL, it is possible to set up 16 panels in RGB or white. The temporization of every scene is independently adjustable: more quickly to awake and to stimulate or more slowly for more color and to dissimulate changes.

CE Sign

Accessories for COLOR-e-MOTION Flex LED FIXTURES

The product is controlled via a Wallmount Unit (WMU), a complete easy-to-use system, on the basis of a DMX 512 bus as a 4-channel system (RGBW) and infrared remote control (the IR receiver is integrated in the WMU). Up to 50 elements can be combined, irrespective of length and color, with an overall length of more than 43 m. Up to three groups of luminaires can be controlled individually via one WMU.

CE Sign

Accessories for COLOR-e-MOTION Carre

The product is controlled via a Wallmount Unit (WMU), a complete easy-to-use system, on the basis of a DMX 512 bus as a 4-channel system (RGBW) and infrared remote control (the IR receiver is integrated in the WMU). Up to three groups of luminaires can be controlled individually via one WMU. Up to 50 elements (approx. 3 m²) can be controlled with one WMU, and one OT75 feeds up to 9 Carres.

CE Sign

Accessories for ELLIPSE OSTAR ORIENT

- OSTAR Power supply kit 75 W: 2 wiring lengths of 500 mm + 2 wiring lengths of 1,000 mm + 2 wiring lengths of 2,000 mm. Each equipped with a female connector
- Suitable for EKINOS E OSTAR and ELLIPSE OSTAR
- Plug and play solution
- CE Sign 50-60 Hz

Accessories for EKINOS E OSTAR

- OSTAR Power supply kit 75 W: 2 wiring lengths of 500 mm + 2 wiring lengths of 1,000 mm + 2 wiring lengths of 2,000 mm. Each equipped with a female connector
- Suitable for EKINOS E OSTAR and ELLIPSE OSTAR
- Plug and play solution
- CE Sign 50-60 Hz