



Overview of product data:
5MJ22372XS


SILUETTE, 2x80W, T16, ECG, PMMA, dir, susp.

1/3



Product description

SILUETTE®, diffuser luminaire, primary light steering with: specular reflector, made of aluminium, highly specular, primary anti glare: High Definition Prismatics (HDP®), primary enclosure: enclosure, made of PMMA, transparent, light output: direct beam, primary light characteristic: symmetric, installation mode: surface-mounted, suspended mounting, for 2 x T16 80W, control gear: ECG, with terminal, 5-pole, max. 2.5mm², mains connection: 230V, AC, 50Hz, housing, made of sheet steel, coil coated, metallic grey (RAL 9006), length: 1.492 mm, width: 214 mm, height: 76mm, mounting bracket, made of aluminium, coated, metallic grey (RAL9006), end cap, made of PS, graphite (RAL7037), protection rating (complete): IP50, insulation class (complete): insulation class I (protective earthing), approval mark: CE, ENEC, VDE, protection symbol: D / F, ambient temperature limit for indoor applications: ≤ +25°C, standard: EN 50419, packing unit: 1 piece,




	L	11
T16 14/24W	592	512
T16 28/54W	1192	1112
T16 35/49/80W	1492	1412



Lamps: 2x T16 80W
 Socket: G5
 Wt. (kg): 6.0
 Order No.: 5MJ22372XS
 EAN: 4039806498397

Product data details:
5MJ22372XS
SILUETTE,2x80W,T16,ECG,PMMA,dir,susp.

2/3


Detailed technical description
Key data

- Product type: diffuser luminaire
- Family: SILUETTE®
- Order No.: 5MJ22372XS

Lighting technology | Lamps | Ballast
Components 1
Lighting technology:

- Light control: specular reflector of aluminium, highly specular
- Cover: enclosure, transparent
- Glare reduction: High Definition Primitives (HDP®)
- Symmetry: symmetric distribution
- Light emission: direct distribution
- UGR viewing direction along longitudinal luminaire axis: < 19
- UGR viewing direction along lateral luminaire axis: < 19

Lamps:

- Light source: fluorescent lamp, 2x T16 80W
- Socket: G5
- Supplement: with terminal, without connection cable, without through wiring, without lamps, without fuse

Ballast:

- Ballast: ECG

Material | Colour

- housing: sheet steel, coil coated, metallic grey (RAL 9006), with rapid mounting bracket
- mounting bracket: aluminium, coated, metallic grey (RAL9006), mounting bracket included with supply
- Quantity: 2 pcs.
- end cap: PS, graphite (RAL7037)
- Cover: enclosure of PMMA

Mounting

- Mounting method, mounting location: suspended mounting, surface-mounted, to double wire suspension, to Y-wire suspension, to the ceiling, to the mounting rail, to the wall
- Arrangement: single/continuous arrangement

Electrical Connection

- Connection: terminal, 5-pole, max. 2.5mm²
- Nominal voltage: 230V, AC, 220..240V, 50Hz

Dimensions | Weight

- Length: 1492 mm
- Width: 214 mm
- Height: 76mm
- Weight: 6.0 kg


Approval

- Protection rating: IP50
- Insulation class: insulation class I (protective earthing)
- Protection symbol: D / F
- Permissible ambient temperature: ≤ +25°C
- Standard: EN 50419
- Certification: CE,ENEC,VDE

Dimensions:
5MJ22372XS

SILUETTE,2x80W,T16,ECG,PMMA,dir,susp.

3/3



	L	l1
T16 14/24W	592	512
T16 28/54W	1192	1112
T16 35/49/80W	1492	1412